


# COUNTERSINKS FOR MAGNETIC DRILLS

## DESIGNED TO PRODUCE A CHAMFER ON PRE-DRILLED HOLES.


- ✓ Unequal pitch for a high quality, smooth finish.
- ✓ Minimises cutting force for extended tooling life.
- ✓ The 3-flat shank design provides a firm hold in the chuck, resulting in excellent cutting performance.
- ✓ Featuring a 19 mm shank to suit most magnetic drills.




**Size Range**  
14 mm - 60 mm Ø



**CSK Type**  
Supercoated  
TCT



**Max. Tensile Strength**  
<1600RM  
(N/ mm<sup>2</sup>)




**Perfect for**  
Hardox, Weldox,  
armoured plate,  
aircraft steels, &  
Abro plate.




### turbo™ ENDURANCE+

For the world's toughest materials


PART NUMBER	MIN-MAX BODY SIZE / ANGLE
JEIETCSK-50	14-50 mm Ø, 90°
JEIETCSK-60	14-60 mm Ø, 90°




**Size Range**  
14 mm - 60 mm Ø




**CSK Type**  
TCT



**Max. Tensile Strength**  
<1200RM  
(N/ mm<sup>2</sup>)




**Perfect for**  
Mild & structural  
steel, cast iron,  
stainless steel.




### turbo™ TOUGH

Produce a chamfer on pre-drilled holes


PART NUMBER	MIN-MAX BODY SIZE / ANGLE
JEITCSK-50	14-50 mm Ø, 90°
JEITCSK-60	14-60 mm Ø, 90°




**Size Range**  
4 mm - 55 mm Ø



**CSK Type**  
M2-AL (HSS)



**Max. Tensile Strength**  
<900RM  
(N/ mm<sup>2</sup>)



**Perfect for**  
Aluminium, most  
mild, and structural  
steels.




### turbo™ STEEL

A 19mm shank suits most magnetic drills

PART NUMBER	MIN-MAX BODY SIZE / ANGLE
JEICSK-25	4-25 mm Ø, 90°
JEICSK-30	4-30 mm Ø, 90°
JEICSK-40	8-40 mm Ø, 90°
JEICSK-50	10-50 mm Ø, 90°
JEICSK-55	12-55 mm Ø, 90°
JEICSK-55/C	12-55 mm Ø, 60°



**Size Range**  
4 mm - 55 mm Ø



**CSK Type**  
M2-AL Coated  
HSS



**Max. Tensile Strength**  
<1000RM  
(N/ mm<sup>2</sup>)



**Perfect for**  
Aluminium, mild,  
structural steel  
with extended  
tool life.



### turbo™ ENDURANCE

Turbo™ Endurance Countersinks

PART NUMBER	MIN-MAX BODY SIZE / ANGLE
JEIECSK-25	4-25 mm Ø, 90°
JEIECSK-30	4-30 mm Ø, 90°
JEIECSK-40	8-40 mm Ø, 90°
JEIECSK-50	10-50 mm Ø, 90°
JEIECSK-55	12-55 mm Ø, 90°
JEIECSK-55/C	12-55 mm Ø, 60°

BOLT SIZE	COUNTERSINK
M10-M14	JEICSK-25
M16-M18	JEICSK-30
M20-M24	JEICSK-40
M26-M30	JEICSK-50
M31-M35	JEICSK-55