



SPECIFICALLY MANUFACTURED FOR CUTTING RAIL TRACK QUICKLY AND EFFECIENTLY.

TCT TOUGH



Size Range 14 mm - 38 mm Ø



Cutting Depth 25 mm



Cutter TypeTCT Rail (Uncoated)



Max. Tensile Strength <1200RM (N/mm²)



Perfect For Rail Track

- Cuts through the most challenging materials.
- Premium grade tungsten carbide teeth.
- Fewer tool changes = less down time.
- Low cost per hole ratio.



TCT SUPER TOUGH



Size Range 14 mm - 38 mm Ø



Cutting Depth 25 mm



Cutter Type TCT Super Rail (Coated)




Max. Tensile Strength <1600RM (N/mm²)



Perfect For All types of Rail Track

- Cuts through the most challenging materials.
- Greater protection from heat build and surface softening.
- Super tough coating for unrivalled performance.
- Fewer tool changes = less down time.
- Low cost per hole ratio.



ТҮРЕ	PART CODE	DEPTH OF CUT	AVAILABLE Ø
TCT RAIL	JEIRCS**	25 mm	14-38 mm
TCT SUPER TOUGH	JEIRCSE**	25 mm	14-38 mm

^{**}Denotes diameter



