FABRICATION REAMERS

THE PERFECT SOLUTION TO CORRECT THE HOLE WHEN THE BOLT DOESN'T FIT.

19 MM SHANK BRIDGE REAMERS - IDEAL FOR MAGNETIC DRILLING MACHINES.





Size Range 14 mm - 32 mm Ø



Max. Tensile Strength <900N/mm²



Shank Size 19.05 mm Ø



Perfect for Steel construction, bridgework



For use with Magnetic drill, Impact reamer (with adaptor)





IMPACT SOCKET ADAPTORS

Our 1/2" and 3/4" drive impact socket adaptors for JEI Turbo™ Bridge Reamers. These reamers and taps have a 19 mm shank designed for use with an impact wrench.

Part Number: 1/2" JEIHEXS

Part Number: 3/4" JEIHEXL



SIZE Ø	MAX HOLE DEPTH	START Ø	FLUTE LENGTH	PART NUMBER
14 mm	52 mm	7 mm	140 mm	JEITBR14
18 mm	61 mm	9.5 2 mm	165 mm	JEITBR18
20 mm	62 mm	11 mm	178 mm	JEITBR20
22 mm	62 mm	13 mm	178 mm	JEITBR22
24 mm	63 mm	15 mm	178 mm	JEITBR24
26 mm	67 mm	16 mm	178 mm	JEITBR26
28 mm	67 mm	18.5 mm	178 mm	JEITBR28
30 mm	64 mm	21 mm	178 mm	JEITBR30
32 mm	64 mm	22.5 mm	178 mm	JEITBR32



3 PIECE TURBO™ BRIDGE REAMER KIT

Part Number - JEITBR-SET3

Includes: 14, 18, and 22 mm. Hex socket adaptors available separately.



5 PIECE TURBO™ BRIDGE REAMER KIT

Part Number - JEITBR-SET5

Includes 14, 18, 22, 26 and 32 mm. Hex socket adaptors available separately.