turbo ENDURANCE



M2-AL HSS COATED CUTTERS CUT TING DEPTH

TO 3 X MORE CUTTING LIFE THAN A STANDARD HSS CUTTER.

A HIGH-QUALITY, CNC-GROUND M2-AL CUTTER FEATURES AN INNOVATIVE COATING THAT DELIVERS **EXCEPTIONAL TOOL LIFE.**

> Diameter Range Ø 10 mm - 65 mm



Shank Size: 19.05 mm - 3/4"

Cutting Depth: 25 mm



Size Range 10 mm - 65 mm Ø



Cutting Depths 25 mm / 50 mm



Cutter Type M2-AL Coated (HSS)



Max. Tensile Strength <1000RM (N/mm²)



Perfect For Aluminium, most mild, and structural steel with

19.05 mm - 3/4' Shank Size:



For use with Magnetic drilling machines

Diameter Range Ø 10 mm - 65 mm



Cutting Depth: 50 mm

- Greater protection from heat build and surface softening.
- Unrivalled performance = less production down time.
- Ability to drill dry when required.
- Low cost per hole ratio.

PART CODE	DEPTH OF CUT	AVAILABLE Ø IN 1MM INCREMENTS
JEIECS**	1″	12-65 mm
JEIECL**	2"	12-65 mm

**Denotes diameter

Other sizes available on request.



5 PIECE 25 MM

Part Number: JEIECS-SET 5

Includes:

- · 1 of each: 14, 16, 18, 20, & 22 mm X 25 mm cutting depth.
- · Pilot pin to suit.



5 PIECE 50 MM

Part Number: JEIECL-SET 5

Includes:

- · 1 of each: 14, 16, 18, 20, & 22 mm X 50 mm cutting depth.
- · Pilot pin to suit.