

MAGBEAST®



MAGBEAST® PREMIUM PRO-122T

HEAVY-DUTY, HIGH PERFORMANCE, 3MT.

Four speed gearbox with continuous speed adjustment allows to set the optimal speed depending on diameter, steel grade or tool quality. Intelligent speed control system maintains constant motor speed regardless of changing loads. Innovative 360-degree LED indicator facilitates proper machine operation and increases work safety.

- ✓ 2300W motor - the most powerful in its class.
- ✓ Intelligent speed control system maintains stable speed.
- ✓ Tapping of through and blind holes.
- ✓ Drilling with TCT or HSS cutters, or twist drill up to 31.75mm.
- ✓ Electronic speed control.
- ✓ Electronic clutch.
- ✓ Rigid design extends tool life.
- ✓ 360-degree visual monitoring system.



UK CA | CE

MagBeast® Premium PRO-122T SPECIFICATIONS



Part no' DRILL-PRO122T/1 ⚡ 110 V
Part no' DRILL-PRO122T/2 ⚡ 240 V

| | |
|---------------------------|--|
| Motor Speeds (under load) | 75-110 rpm (gear 1) / 135-200 rpm (gear 2) / 220-320 rpm (gear 3) / 390-570 rpm (gear 4) |
| Motor Power | 2300 W |
| Weight | 25 kg (55lbs) |
| Max cutter capacity | 120 mm (4.72")* |
| Max twist drill capacity | 31.75 mm (1-1/4") |
| Tapping size | M30 (1-1/4") |
| Stroke | 225 mm (9") |
| Max depth of cut | 100 mm (4") |
| Voltage | 1- 220-240 V, 50-60 Hz DRILL-PRO122T/1 1- 110-120 V, 50-60 Hz DRILL-PRO122T/2 |
| Magnetic clamping force | 1835 kG (18,000 N) |
| Magnetic Base Dimensions | 110 mm x 220 mm x 50 mm 4.3" x 8.7" x 2" |
| Min. Workpiece Thickness | 10 mm (3/8") |
| Spindle | MT3 |
| Tool holder | 19 mm (3/4") or 32 mm (1-1/4") Weldon |



Intuitive control panel at top of the drill.



Cutter capacity up to 120 mm (4.72").
Max depth of cut up to 100 mm (4").



Counterclockwise (CCW) rotation.
User-friendly control of tapping tool release.



Through hole tapping up to M30.

360-DEGREE VISUAL MONITORING SYSTEM (VMS)

For hassle free drilling.

