Drilling Machine Solutions



Part no' DRILL-LP45/1 / 110 V Part no' DRILL-LP45/2 / 240 V

Designed to fit into the most height restrictive areas. Ideal for bridge maintenance work & repairs, platform drilling, steel construction.



Cuts holes up to 45 mm Ø x 50 mm deep



Use JEI's optional Turbo Twist Drills see page 41



Compact only 180 mm height



Convenient carry handle



Ratchet handle for left or right sided operation





Features / Benefits:

- Compact design only 180 mm high.
- Big capacity will handle up to 45 mm diameter holes through 50 mm plate.
- Convenient ratchet handle can be used in either a left or right hand position.
- 12 mm twist drill capacity.
 - Maintenance free no adjustable slides, no exposed motor cord.



Ratchet handle.

- Safety chain.
- Safety guard.
- Coolant bottle assembly.
- 2.5 mm and 5 mm Allen key.

Œ

- Plastic carrying case.
- Operators manual.

SPECIFICATIONS

| MODEL | LP45 |
|----------------------|---|
| Spindle | 19 mm |
| Weight | 11 kg |
| Max Stroke | 63 mm |
| Cutter Capacity | 45 mm Ø x 2" depth of cut |
| Twist Drill Capacity | 12 mm Ø with optional Turbo Twist drills (see page 41) |
| Countersink Capacity | 30 mm |
| Motor | 1010 W |
| RPM | 1 Fixed Speed |
| | no load 500 RPM |
| | loaded 290 RPM |
| Height | 180 mm |
| Length x Width | 310 x 125 mm |
| Magnetic Base L x W | 180 x 85 mm |
| Magnet Deadlift | 1200 kg on 1" Plate (11700 N) |
| Noise Level | < 90dB |
| Vibration Level | < 2.5 m/s ² |
| Voltage/ Part no | 110 V - DRILL-LP45/1 |
| | 240 V - DRILL-LP45/2 |
| Shipping Weight | 19 kg |
| Shipping Dimensions | 360 x 350 x 260 mm |